



il parquet dal 1910

## DESCRIPTION OF PERFORMANCE N° GA2SMILE10 S3-C

### 1. Product type

- Wood flooring “PRONTO PARQUET SMILE”
- Product: engineered wood flooring (two ply) with tongue & groove joint, lacquered.
- Available wood species: Oak
- Total thickness (mm): 10
- Product identification: see shipping document (Documento di trasporto)

### 2. Intended use

Interior use

- Fully glued installation: for all products with thickness 10mm.

### 3. Producer

Gazzotti Spa - Via Lame, 282 - 40013 Trebbo di Reno (BO) - Italy

### 4. System of conformity

System 4

### 5. Harmonized technical standard

EN 14342:2013

### 6. Declared performance

Essential features	Performance	Harmonized standard
Fire resistance class (*)	Cfl – s1	EN 14342:2013
Emission of formaldehyde	E1	
Emission of pentachlorophenol	≤ 5 ppm	
Breaking strength (maximum load)	NPD	
Slipperiness	NPD	
Thermal resistance	0.063 m <sup>2</sup> K/W	
Biological durability	CLASS 1	

(\*) as per table 1 of standard EN 14342:2013, for an average minimum density of 500 Kg/m<sup>3</sup>

Signed for and behalf of the manufacturer Gazzotti Spa by:

**Ing. Andrea Signoretti**

(Head of Operations)

Trebbo di Reno (BO) - 01.09.2015